

LG Hausys floors

Technical Specification

LG Hausys floors [RCB Tile] : Rigid LVT 6.0 (Attached 1.5mm Underlayment)

Technical Data

Characteristic	Standard	Unit	6.0T (W/L 0.55mm)
Type of Flooring	EN ISO 10582	-	PVC Heterogeneous
Classification	EN 685	-	Class 23/33/42
Size		%	≤0.15
Straightness & Squareness	EN ISO 24342	mm	≤0.35
Overall Thickness	EN ISO 24346	mm	6.0
Wear Layer Thickness	EN ISO 24340	mm	0.55
Dimensional stability	EN 434	%	≤0.1
Abrasion rating	EN 660-2	-	Group T
Residual indentation	EN ISO 24343-1	mm	≤0.05
Furniture leg	EN424	-	No damage
Castor chair	EN425	-	No damage
Curl resistant to heat	EN434	-	≤ 2
Impact sound reduction	EN ISO 140-8	-	ΔLw ≥ 19dB (With Underlayment)
Thermal performance	EN12667	m ² K/W	≤0.1
Light fastness	EN ISO105-B02	-	≤6
Chemical resistance	EN423	-	No Change
Electrical propensity	EN1815	-	Pass
Reaction to fire	AS ISO9239-1:2003, EN13501-1	-	Bfl-s1
Slip resistance	AS4586-2013	-	R10

Product Standard : ISO 10582

